



DRD-A

Digital Rotary Dimmer

Features

- * For DALI Systems
- * Available for Assigned Group Mode/Broadcast Mode
- * On/Off Switchable Function
- * Green LED Locator Light
- * Automatic Synchronization Makes It Possible to Change the Control Location Without Disturbing Effects (Brightness /OnOff)
- * Minimum Brightness Setting
- * Power Supply Via DALI Bus



DRD-A Operation



- * On/Off – Press
- * Brightness Decrease – Left Rotate
- * Brightness Increase – Right Rotate

Function

Dimming(Direct Arc Power Control) · Minimum Brightness setting

Specifications

Power Input Via Voltage DALI Bus 10.5-22.5Vdc
 Current Draw 15mA form DALI
 Operating Temperature 0-50°C

Setting Group or Broadcast Mode



0	1	2	3
Broadcast	Group1	Group2	Group3
4	5	6	7
Group4	Group5	Group6	Group7
8	9	A	B
Group8	Group9	Group10	Group11
C	D	E	F
Group12	Group13	Group14	Group15

Note:

1. Group 1 represents the Group 0 in the DALI standard.

Mechanical Drawing

All Dimensions in Inches(mm)
 Tolerance Inches: x.xxx=±0.02
 Millimeters: x.xx=±0.5

